


TOKYO DALI

CCT SWITCH - ZOOM




TOKYO 15 DALI

	W	K	Real lm (2700K)	Real lm (3000K)	Real lm (4000K)	△	ØxL (mm.)	Kg
○ 1.5005.3118 ● 1.5005.3218	15	2K7-3K-4K	955 (15°) 1080 (55°)	985 (15°) 1115 (55°)	1060 (15°) 1200 (55°)	15°-55°	70x160	0,67



Accesorios Accessories Accessoires

● 1.5005.8001 Honeycomb Tokyo 15




TOKYO 30 DALI

	W	K	Real lm (2700K)	Real lm (3000K)	Real lm (4000K)	△	ØxL (mm.)	Kg
○ 1.5006.3118 ● 1.5006.3218	30	2K7-3K-4K	1800 (15°) 1955 (55°)	1860 (15°) 2025 (55°)	2000 (15°) 2175 (55°)	15°-55°	85x165	0,95

DETALLES DETAILS DÉTAILS



Switch ajustable de temperatura
Adjustable temperature switch
Régulateur de température



Haz de luz ajustable
Adjustable beam angle
Faisceau de lumière réglable



Driver DALI integrado en carril
DALI driver integrated in rail
Driver DALI intégré dans le rail



Acc. carril DALI pág. 130-131
Track DALI acc. pages 130-131
Acc. rail DALI pages 130-131